VENTO MULTI

Power: 15 / 20 / 25 / 35 / 50 kW

FUEL PELLETS, SILVERS, BRIQUETTE, SHAVINGS

- Atested steel 6 mm
- Cast-iron burner with moving grates
- Modern multi-functional controller
- Effective burning of many kinds of biomass
- Automatic ash removal system (option)

Vento Multi is a modern technology that meets the economics of heating and ecology, created for large homes.

It is also ideal for industrial facilities and public facilities with relatively small areas.

It is a combination of automation and usability, giving independence. In a maintenance-free system, it burns biomass (saw-dust, wood chips, pellets, briquettes) but also has the option of switching to solid fuel combustion (coal, wood).

An ideal solution for those who do not have a sustainable source of fuel, but in parallel, they care about the low-emission, compatible with the guidelines of standard EN 303-5.

VENTO MULTI		15 kW	20 kW	25 kW	35 kW	50 kW
Effectiveness	%	86				
Water capacity	L	67	80	95	120	137
Fuel tank capacity	m^3	0,6 and 1			1	1
Working temperature of boiler water	℃	70 - 80				
Minimum temperature of water on the return	℃	55				
Working pressure	bar	Max. 1,5				
Power supply	V	230				
Dimensions of loading opening (manual loading)	mm	178 x 313			188 x 453	
Type of burner		Cast-iron / moving grates				
Chimney height	m	8 - 10				
Minimum cross-section of chimney	cm^2 / Ømm	324/180		400/200	625/250	

The given electrical powers are the powers of the devices installed in the boilers

Due to the constant process of improvement and modernization of products by Moderator, the technical data of manufactured devices may differ from those given at www.moderator.com.pl